

# Dry Pigment Ready Mix Color Card

Solomon Colors



## SGS Integral Colors

These color chips represent shades of Integral Colors based on medium tone gray Type I-II Portland cement with 4" slump. Use this chart as a guideline only. The colors may not exactly represent the final color. Shade variations of cement and aggregate plus variations in the volume of water, the addition of admixtures and other additives may have an effect on the design mix and final color. We recommend that a test slab be poured and approved prior to the start of the job.

1 - 25lb. bag per 4 yards/1.04 lb. sack	1 - 25lb. bag per 2 yards/2.08 lb. sack	1 - 25lb. bag per 1 yards/4.16 lb. sack	1 - 25lb. bag per 4 yards/1.04 lb. sack	1 - 25lb. bag per 2 yards/2.08 lb. sack	1 - 25lb. bag per 1 yards/4.16 lb. sack
413 Colony Red	413 Clay	413 Terra Cotta	306 Canvas	306 Toffee	306 Cinnamon
417 Rose	417 Brick Red	417 Apple Red	238 Thyme	238 Doeskin	238 Marigold
489 Dusty Rose	489 Light Plum	489 Dark Redwood	338 Earthen	338 Rawhide	338 Leather
288 Rosemary	288 Ginger	288 Straw	385 Taupe	385 Lava	385 Bark
750 Desert Tan	750 Salmon	750 Peach	242 Sandstone	242 Sahara	242 Nutmeg
366 Blush	366 Dk. Blush	366 Natural Red	5092 Olive	5092 Sage	5092 Avocado
775 Sand	775 Cedar	775 Sedona	920 Slate	920 Smoke	920 Onyx
			1 - 25lb. bag per 4 yards	1 - 25lb. bag per 3 yards	1 - 25lb. bag per 2 yards
755 Trail Dust	755 Driftwood	755 Apricot			
			*908 Lunar Eclipse	*908 Asphalt	*908 Ultra Black

Dry Pigment Ready Mix Color Card



Color Selection Chart A-132.02

## LITHOCHROME® Color Hardener, LITHOCHROME® Antiquing Release & SCOFIELD® Texturetop®

### PRODUCT DESCRIPTIONS:

**LITHOCHROME® Color Hardener** is a dry-shake colored hardener formulated to be easily incorporated into the surface of freshly placed concrete.

**LITHOCHROME® Antiquing Release** is a powdered, colored bond breaker used when imprinting with mat-type texturing skins or stamping tools.

**SCOFIELD® Texturetop®** is a trowelable cementitious topping for resurfacing and texturing nonmoving, interior or exterior concrete floors or hardscapes.

**LITHOCHROME® Colorwax™ & COLORCURE® Concrete Sealer** are available in matching colors.

**Additional colors available:**  
A-11 Concrete Gray, 6016 White, 0510 Black.

Review Tech-Data Bulletins and MSDS before use. Visit [www.scofield.com](http://www.scofield.com) for the most current versions.

A-53 Arizona Tan	0266 Ash White *	1138-S Blue Smoke+SS	A-59 Beige Cream *
0568 Blush Beige *	A-26 Brick Red	1139 Burberry Beige *	A-33 Classic Gray
A-27 Dark Red	A-21 Deep Charcoal	A-25 La Crescenta Brown	3611 Oyster White *
A-55 Pecan Tan	A-57 Platinum Gray	A-24 Russet	4471 Saddle Brown
A-50 Slate Gray	4948 Smoke Beige *	A-51 Steadman Buff	5183 Stone Gray *
A-29 Terra Cotta	A-28 Tile Red	5921 Walnut	5758 Weathered Sage *

**COVERAGE RATE FOR COLOR HARDENER:** Coverage rates vary with intended use and application. LITHOCHROME Color Hardener should be applied at a rate of 60 lb (1 bag) per 100 ft<sup>2</sup> (3.0 kg/m<sup>2</sup>), except where indicated by an asterisk (\*). \*Denotes colors requiring a higher coverage rate, where Scofield recommends 90-120 lb per 100 ft<sup>2</sup> (4.5-6.0 kg/m<sup>2</sup>). See reverse for more information. +SS = Check current market price.

Colors are approximate and best viewed in daylight. Colors shown represent the use of LITHOCHROME Color Hardener with a flat-troweled finish which has been cured with color-matched LITHOCHROME Colorwax or COLORCURE Concrete Sealer.

L. M. Scofield Company 1 800 800 9900

FOR PROFESSIONAL USE ONLY

## JMS CONCRETE STAMP DESIGNS

CONCRETE & EXCAVATING



Random Stone



Seamless Slate




Wood Plank



Small Ashlar Slate




Brick Border



Large Ashlar Slate



Square Slate Border



Herringbone Pattern